


# Hideaway HSA 300

HSA - HIDEAWAY SURFACE ACCESS  
ENCLOSURE WITH  
AV CONNECTIVITY, AC POWER,  
AND USB POWER




USA


- ▶ Provides convenient access to HDMI, VGA, Stereo Audio, and Network connectivity
- ▶ Provides two 5 VDC USB power outlets and up to 2.1 A / 10.5 watts of power for charging mobile devices
- ▶ Unswitched AC power outlets available for US, Europe, and other world markets
- ▶ Available Multi-Region AC outlet is compatible with a variety of AC plug types
- ▶ Durable mechanic pneumatic movement and mechanical latching mechanism
- ▶ Virtually flush with the furniture surface when closed
- ▶ UL/c-UL listed and CE compliant



US



UK



Central Europe



Multi-Region

The Extron Hideaway® HSA 300 is a compact, tilt-up, furniture mountable enclosure for convenient access to AV connectivity, AC power, and USB power. It offers a perfect blend of connectivity and design aesthetics that complements sophisticated board rooms, conference rooms, and training facilities.



**Extron Electronics**  
INTERFACING, SWITCHING AND CONTROL


## DESCRIPTION

The Extron **Hideaway® HSA 300** is a compact, tilt-up, furniture-mountable enclosure for inconspicuous access to AV connectivity, AC power, and USB power. The HSA 300 features connectors for HDMI, VGA, Stereo Audio, and Network signals, one unswitched AC outlet, and two 5 VDC USB power outlets for charging mobile devices such as smartphones or tablets. When closed, the HSA 300 sits virtually flush with the table surface. To open, press the top of the enclosure and the HSA 300 slowly pivots into view, presenting the connectors at an ergonomic 49 degree angle to the tabletop. The HSA 300 is available with one US, UK, Central Europe, or Multi-Region AC outlet that's compatible with a variety of AC plug types. The HSA 300 is available in a durable black anodized finish to complement most furniture styles and room decor.

## FEATURES

- ▶ Provides convenient access to HDMI, VGA, Stereo Audio, and Network connectivity
- ▶ Provides two 5 VDC USB power outlets and up to 2.1 A / 10.5 watts of power for charging mobile devices
- ▶ Unswitched AC power outlets available for US, Europe, and other world markets
- ▶ Available Multi-Region AC outlet is compatible with a variety of AC plug types
- ▶ Durable mechanic pneumatic movement and mechanical latching mechanism
- ▶ Virtually flush with the furniture surface when closed
- ▶ UL/c-UL listed and CE compliant

## APPLICATION DIAGRAM



## SPECIFICATIONS

VIDEO INPUT/OUTPUT		
Number/signal type	1 pass-through VGA 1 pass-through HDMI	
Connectors	15-pin HD female to 15-pin HD female on a 6" (15 cm) pigtail HDMI female to HDMI female on a 10" (25 cm) pigtail	
AUDIO INPUT/OUTPUT		
Number/signal type	1 pass-through stereo, unbalanced	
Connectors	3.5 mm TRS jack to 3.5 mm 3 pole captive screw connector on a 10" (25 cm) pigtail	
DATA INPUT/OUTPUT		
Standards	CAT 6, TIA/EIA T568B	
Connectors	1 female RJ-45 to 1 female RJ-45	
GENERAL		
<b>Power</b>		
HSA 300 (US)	125 VAC, 50-60 Hz, 12 A max.	
HSA 300 (EU/Multi-Region/UK)	240 VAC, 50-60 Hz, 10 A max.	
<b>USB power</b>		
Power supply	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 1 A USB: 5 VDC, 2.1 A, 10.5 watts total	
Power output		
<b>Mounting</b>		
Furniture mount	Yes	
Min./max. table thickness	0.375" to 3.00" (0.95 cm to 7.62 cm)	
Enclosure type	Metal	
Enclosure dimensions		
<b>CAUTION:</b> Use the appropriate metal Extron routing template or refer to the surface cutout dimensions here before cutting a hole in the furniture or other surface. Pay special attention to the direction the unit will face. The connector access side of the unit is <u>underlined</u> . Extron is not responsible for miscut mounting holes.		
<b>HSA 300 — all models</b>		
Top plate (outer rim)	<u>8.18"</u> W x 6.375" D ( <u>20.79</u> cm W x 16.19 cm D)	
Top plate (inside tilt plate)	<u>5.90"</u> W x 4.10" D ( <u>14.99</u> cm W x 10.41 cm D)	
Surface cutout (inside rim)	<u>7.70</u> +0.00/-0.02" W x 5.90 +0.00/-0.02" D ( <u>19.56</u> +0.00/-0.05 +cm W x 14.99 0.00/-0.05 +cm D)	
Box (under surface)	4.0" H x <u>6.3"</u> W (front of unit) x 5.0" D (10.2 cm H x <u>15.9</u> cm W x 12.7 cm D) without clamps 4.0" H x <u>10.0"</u> W (front of unit) x 5.0" D (10.2 cm H x <u>25.3</u> cm W x 12.7 cm D) with clamps	
Product weight	5.0 lbs (2.3 kg)	
Vibration	ISTA 1A in carton (International Safe Transit Association)	
Regulatory compliance		
Safety	CE, c-UL, CSA C/US, UL	
Warranty	3 years parts and labor	
<b>NOTE:</b> All nominal levels are at ±10%.		
<b>Model</b>	<b>Version Description</b>	<b>Part number</b>
HSA 300 US	US Outlet	60-1422-0A
HSA 300 UK	UK Outlet	60-1422-0B
HSA 300 EU	EU Outlet	60-1422-0D
HSA 300 MULTI	Multi-Region Outlet	60-1422-0J

For complete specifications, please go to [www.extron.com](http://www.extron.com)  
Specifications are subject to change without notice.

### Worldwide Sales Offices

Anaheim • Raleigh • Silicon Valley • Dallas • New York • Washington, DC • Toronto • Mexico City • Paris • London • Frankfurt  
Amersfoort • Moscow • Dubai • Johannesburg • New Delhi • Bangalore • Singapore • Seoul • Shanghai • Beijing • Tokyo

#### UNITED STATES

+800.633.9876  
Inside USA/Canada  
+1.714.491.1500

#### EUROPE

+800.3987.6673  
Inside Europe  
+31.33.453.4040

#### ASIA

+800.7339.8766  
Inside Asia  
+65.6383.4400

#### MIDDLE EAST

+971.4.299.1800