

# Specifications — CCR 204, CCR 306

---

## Switch contact closure

Quantity/type	
CCR 204 .....	4 normally open switches
CCR 306 .....	6 normally open switches
Connectors	
CCR 204 .....	(1) 3.5 mm captive screw connector, 5 pole
CCR 306 .....	(1) 3.5 mm captive screw connector, 3 pole (1) 3.5 mm captive screw connector, 5 pole
Contact rating .....	50 VDC, 25 mA
Pin configurations	
CCR 204 .....	Pins 1, 2, 3, 4 = switches 1, 2, 3, 4; pin 5 = GND
CCR 306 .....	3 pole connector: pin 1 = switch 1, pin 2 = switch 2, pin 3 = GND 5 pole connector: pins 1, 2, 3, 4 = switches 3, 4, 5, 6; pin 5 = GND

**NOTE** Each switch can be used to select an input on a connected switcher. See the CCR's installation instructions for details.

## General

Temperature/humidity .....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Mounting	
Furniture mount .....	Yes
Enclosure type .....	Metal
Enclosure dimensions	
CCR 204	
Faceplate .....	1.75" H x 4.0" W x 0.1" D (4.4 cm H x 10.2 cm W x 0.3 cm D)
Device .....	1.4" H x 2.6" W x 1.2" D (3.4 cm H x 6.6 cm W x 3.0 cm D) (Depth excludes buttons. Allow at least 1.65" [4.2 cm] depth in the wall or furniture for device and cable clearance.)
CCR 306	
Faceplate .....	2.1" H x 4.0" W x 0.1" D (5.3 cm H x 10.2 cm W x 0.3 cm D)
Device .....	1.4" H x 2.6" W x 1.2" D (3.4 cm H x 6.6 cm W x 3.0 cm D) (Depth excludes buttons. Allow at least 1.65" [4.2 cm] depth in the wall or furniture for device and cable clearance.)
Product weight	
CCR 204 .....	0.1 lb (0.05 kg)
CCR 306 .....	0.1 lb (0.03 kg)
Shipping weight .....	1 lb (<1 kg)
Vibration .....	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Environmental .....	Complies with the appropriate requirements of RoHS, WEEE
Warranty .....	3 years parts and labor

**NOTE** All nominal levels are at  $\pm 10\%$ .

**NOTE** Specifications are subject to change without notice.

7.6-061909-D2-112012