

# Specifications — CCR 4BLB and CCR 2BLB

---

## General

Power input requirements .....	12 VDC, 0.1A supplied by an Extron MediaLink™ Controller or an external power supply
External power supply .....	100 VAC to 240 VAC, 50/60 Hz, external, autoswitchable; to 12 VDC, 1 A, regulated (External power supply is optional.)
Temperature/humidity .....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Rack mount .....	Yes, with optional faceplate, and furniture or wall mountable with optional faceplates or AAP wall plates
Enclosure type .....	Metal
Enclosure dimensions	
Faceplate .....	1.4" H x 3.5 W x 0.1" D (3.5 cm H x 8.9 cm W x 0.3 cm D) (double space AAP)
Device .....	1.4" H x 3.5" W x 0.8" D (3.5 cm H x 8.9 cm W x 2 cm D) (Depth excludes connectors and buttons.)
Product weight	
CCR 2BLB .....	0.1 lbs (<0.1 kg)
CCR 4BLB .....	0.12 lbs (<0.1 kg)
Shipping weight	
CCR 2BLB .....	0.4 lbs (<0.2 kg)
CCR 4BLB .....	0.42 lbs (<0.2 kg)
Vibration .....	ISTA 1A in carton (International Safe Transit Association)
Listings .....	UL, CUL
Compliances .....	CE, FCC Class A, VCCI, AS/NZS, ICES
Warranty .....	3 years parts and labor

**NOTE** All nominal levels are at ±10%.

**NOTE** Specifications are subject to change without notice.

7.52-030107-D1 -111512