

Specifications — Cable Cubby® 200

General

NOTE The Universal AC outlet is fully compatible with Europlug, British, Indian, Danish, and Italian plug types. See the Universal AC outlet guide on the Extron Web site, www.extron.com, for compatibility details on all plug types.


NOTE Architectural Adapter Plates (AAPs) are shown in diagrams and in photographs as examples only. AAPs are optional accessories for the Cable Cubby products. AAPs and cables must be ordered separately.

Mounting

Furniture mount..... Yes
Min./max. table thickness 0.375" (0.95 cm), minimum
Enclosure type Metal
Enclosure dimensions

CAUTION Use the appropriate metal Extron routing template or refer to the surface cutout dimensions here before cutting a hole in the furniture or other surface. Pay special attention to the direction the unit will face; the unit's AAP and connector access side is underlined. Extron is not responsible for miscut mounting holes.

Top plate (outer rim)..... 8.00" W x 4.39" D
(20.32 cm W x 11.16 cm D)
Surface cutout (inside rim). 7.33 +0.00/-0.02" W x 3.17 +0.00/-0.02" D
(18.62 +0.00/-0.05 cm W x 8.05 +0.00/-0.05 cm D)
Box (under surface)..... 4.00 " H x 7.12" W (front/rear of unit) x 2.974" D
(10.16 cm H x 18.08 cm W x 7.55 cm D)



Cable Cubby 200

Cable AAP cable hole diameters

Large cable hole..... 0.63" (1.60 cm)
Large grommet 0.45" (1.14 cm)
Medium cable hole..... 0.56" (1.42 cm)
Medium grommet 0.39" (0.99 cm)
Small cable hole 0.50" (1.27 cm)
Small grommet 0.31" (0.79 cm)
Product weight 2.5 lbs (1.1 kg)
Shipping weight 4 lbs (2 kg)
Vibration..... ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance
Safety..... CE, CSA C/US, c-UL, UL
Warranty 3 years parts and labor

NOTE Specifications are subject to change without notice.

7.6-111609-D12