

Specifications — D/2 DA4 DVI

Video

| | |
|-------------------------|--|
| Maximum bit rate | 4.95 gigabits/second total (1.6 gigabits/second/color) |
| Maximum bandwidth | 165 MHz |

Video input

| | |
|-----------------------------|--|
| Number/signal type | 1 single-link DVI-D |
| Connectors | 1 attached cable with male DVI-D connector |
| Minimum input voltage | 0.15 V _{p-p} |
| Resolution range | Up to 1920x1200 or 1080p @ 60 Hz |

Video signal characteristics

| | |
|----------------------|------------------------|
| Rise/fall time | 220 ps, maximum 350 ps |
|----------------------|------------------------|

Video output

| | |
|--------------------------|----------------------------------|
| Number/signal type | 4 single-link DVI-D |
| Connectors | 4 female DVI-D |
| Minimum level | 0.6 V _{p-p} |
| Resolution range | Up to 1920x1200 or 1080p @ 60 Hz |

DDC and HDCP communication

| | |
|----------------------------|-----------------------|
| DDC and HDCP signals | Connected to output 1 |
|----------------------------|-----------------------|

General

| | |
|----------------------------|--|
| Power | 100 VAC to 240 VAC, 50/60 Hz, 13 watts, internal, autoswitchable |
| Temperature/humidity | Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing |
| Rack mount | Yes, with optional 1U rack shelf, part #60-190-01 or 60-604-01 |
| Enclosure type | Metal |
| Enclosure dimensions | 1.75" H x 8.75" W x 9.4" D (1U high, half rack wide) 4.4 cm H x 22.2 cm W x 23.9 cm D (Depth excludes connectors.) |
| Product weight | 2.8 lbs (1.3 kg) |
| Shipping weight | 5 lbs (3 kg) |
| Vibration | ISTA 1A in carton (International Safe Transit Association) |
| Listings | UL, CUL |
| Compliances | CE |
| Warranty | 3 years parts and labor |

NOTE All nominal levels are at ±10%.

NOTE Specifications are subject to change without notice.

7.52-072607-D5-111612