

Specifications — D/2 DA4, D/2 DA4 DVI Direct Digital DAs

Video

Bit rate 1.6 gigabits/second/color

Video input

Number 1 DFP or DVI

Connectors D/2 DA4 1 attached cable with DFP male connector
D/2 DA4 DVI 1 attached cable with DVI male connector

Minimum input voltage 0.15V p-p

Video signal characteristics

Rise/fall time 220 pS, maximum 350 pS

Video output

Number 4 DFP or DVI

Connectors D/2 DA4 4 DFP female
D/2 DA4 DVI 4 DVI female

Minimum output voltage 0.6V p-p

General

Power 100VAC to 240VAC, 50/60 Hz, 13 watts, internal, auto-switchable

Temperature/humidity Storage -40° to +158°F (-40° to +70°C) / 10% to 90%, non-condensing
Operating +32° to +122°F (0° to +50°C) / 10% to 90%, non-condensing

Rack mount Yes, with optional rack shelf, part #60-190-01

Enclosure type Metal

Enclosure dimensions 1.75" H x 8.75" W x 9.4" D (1U high, 1/2 rack width)
4.4 cm H x 22.2 cm W x 23.9 cm D

Product weight

D/2 DA4 2.6 lbs (1.2 kg)

D/2 DA4 DVI 2.8 lbs (1.3 kg)

Shipping weight 5 lbs (2.3 kg)

Vibration ISTA/NSTA 1A in carton (International Safe Transit Association)

Listings UL, CUL

Compliances CE

Warranty 3 years parts and labor

NOTE *Specifications are subject to change without notice.*

7.31-110501-D1 " #! " #