

Specifications



Flex55 SuperPlate Series




General

Mounting	Mounts to Flex55 frames and enclosures.
Connector type.....	HDMI female to female pigtail cable, 12.75" (324 mm) VGA female to female pigtail cable, 9.00" (228 mm) DisplayPort female to female pigtail cable, 13.30" (338 mm) 3.5 mm stereo audio jack to captive screw pigtail cable, 10.25" (260 mm) USB A female to female pigtail cable, 12.30" (312 mm)
Resolution range.....	HDMI cable: Up to 4K @ 60 Hz (4096x2160) or UHD @ 60 Hz (3840x2160) 8 bit color depth, max. 18.0 Gbps data rate
Faceplate dimensions	2.17" H x 2.17" W x 0.29" D (55.0 mm H x 55.0 mm W x 7.3 mm D) Allow 1.85" (47 mm) depth for cable management.

SuperPlate 100





Front




Side

SuperPlate 120





Front




Side

SuperPlate 140





Front




Side

SuperPlate 150



Front



Side

Material.....	High-impact plastic blend
Product weight	
SuperPlate 100	0.25 lb (0.12 kg)
SuperPlate 120	0.26 lb (0.12 kg)
SuperPlate 140	0.20 lb (0.09 kg)
SuperPlate 150	0.11 lb (0.05 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety	CE
Environmental.....	Complies with the appropriate requirements of RoHS, WEEE
Warranty	3 years parts and labor

NOTE: Specifications are subject to change without notice.

NOTE: Shipping dimensions and weights are available at www.extron.com.

8.1-072216-D1