

Specifications

HDMI DA Series

NOTE: *Appropriate DVI-D to HDMI cables or adapters are required for DVI signal input/output.

Video

Maximum data rate.....	6.75 Gbps (2.25 Gbps per color)
Maximum pixel clock.....	165 MHz
Resolution range	Up to 1920x1200 or 1080p @ 60 Hz, 12-bit color
Formats.....	RGB and YCbCr digital video
Standards.....	DVI 1.0, HDMI, HDCP

Video input

Number/signal type	1 single link HDMI (or DVI-D*)
Connectors	1 female 19-pin HDMI type A

Video output

Number/signal type	
HDMI DA2	2 single link HDMI (or DVI-D*)
HDMI DA4.....	4 single link HDMI (or DVI-D*)
HDMI DA6.....	6 single link HDMI (or DVI-D*)
Connectors	
HDMI DA2.....	2 female 19-pin HDMI type A
HDMI DA4.....	4 female 19-pin HDMI type A
HDMI DA6.....	6 female 19-pin HDMI type A

Control/remote

Serial control port.....	RS-232, 3.5 mm, 3-pole captive screw connector
Baud rate and protocol.....	9600 baud, 8 data bits, 1 stop bit, non-parity
Serial control pin configuration.....	1 = Tx, 2 = Rx, 3 = GND
USB control port.....	1 front panel, female, mini USB B
USB standards	USB 2.0, low speed
Program control	Extron Simple Instruction Set (SIS™)

General

Power	
HDMI DA2	External
	Input: 100-240 VAC, 50-60 Hz
	Output: 12 VDC, 1 A, 12 watts
HDMI DA4 and HDMI DA6	Internal
	Input: 100-240 VAC, 50-60 Hz

Power consumption	
HDMI DA2	
Device.....	4 watts
Device and power supply ...	5.3 watts
HDMI DA4 and HDMI DA6	7.7 watts

Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, vents on top
Thermal dissipation	
HDMI DA2	
Device	13.1 BTU/hr
Device and power supply ...	17.5 BTU/hr
HDMI DA4 and HDMI DA6	18.2 BTU/hr
Mounting	
Rack mount	Yes, with optional rack shelf kit
Enclosure type	Metal
Enclosure dimensions	
HDMI DA2	1.0" H x 4.3" W x 3.0" D (one quarter rack wide) 2.5 cm H x 10.9 cm W x 7.6 cm D (Depth excludes connectors)
HDMI DA4 and HDMI DA6	1.75" H x 8.75" W x 6.0" D (one half rack wide) 4.4 cm H x 22.2 cm W x 15.2 cm D (Depth excludes connectors)
Product weight	
HDMI DA2	0.35 lbs (0.2 kg)
HDMI DA4 and HDMI DA6	1.6 lbs (0.7 kg)
Shipping weight	
HDMI DA2	2 lbs (1 kg)
HDMI DA4 and HDMI DA6	3 lbs (2 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety	CE, c-UL, UL
EMI/EMC	CE, C-tick, FCC Class A, ICES, VCCI
Environmental	Complies with the appropriate requirements of RoHS, WEEE.
Warranty	3 years parts and labor

NOTE: All nominal levels are at $\pm 10\%$.

NOTE: Specifications are subject to change without notice.

8.0-061913-D3