

Specifications — MCP 1000M, MCP 1000S

Control/remote — control panel

Serial control ports	1 host 9-pin female D connector 1 switcher 9-pin male D connector
Baud rate and protocol	9600 baud, 8 data bits, 1 stop bit, no parity
Serial control pin configurations	2 = TX, 3 = RX, 5 = GND
Extron remote key pad control..	(2) 5 mm, 5-pole captive screw connectors
Program control	Extron's Simple Instruction Set (SIS™)

General

Power

MCP 1000M	100 VAC to 240 VAC, 50/60 Hz, 15 watts, internal, autoswitchable
MCP 1000S	Supplied by the MCP 1000M or the matrix switcher

Temperature/humidity	Storage -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
----------------------------	--

Rack mount	Yes, with included brackets. Also under-furniture mountable or shelf-mountable with included brackets.
------------------	--

Enclosure type	Metal
----------------------	-------

Enclosure dimensions	1.75" H x 17.5" W x 5.0" D (1U high, full rack wide) 4.4 cm H x 44.5 cm W x 12.7 cm D (Depth excludes connectors and knobs. Width excludes rack ears.)
----------------------------	--

Product weight

MCP 1000M	3.0 lbs (1.4 kg)
MCP 1000S	2.5 lbs (1.1 kg)

Shipping weight

MCP 1000M	7 lbs (4 kg)
MCP 1000S	6 lbs (3 kg)

Vibration	ISTA 1A in carton (International Safe Transit Association)
-----------------	--

Listings	UL, CUL
----------------	---------

Certifications	CE, FCC Class A
----------------------	-----------------

Warranty	3 years parts and labor
----------------	-------------------------

NOTE All nominal levels are at $\pm 10\%$.

NOTE Specifications are subject to change without notice.

7.51-082504-D3-111612)