

Specifications — SCP 100P

Control/remote — control pad

IR controller module IR 401 (optional)

General

Power	12VDC, at 60 mA, from the System 5cr Plus switcher
Temperature/humidity	Storage -40° to +158°F (-40° to +70°C) / 10% to 90%, non-condensing Operating +32° to +122°F (0° to +50°C) / 10% to 90%, non-condensing
Rack mount	No, but furniture/wall mountable with included faceplates and electrical boxes or optional mounting bracket kits or AAP wall plates.
Enclosure type	Metal
Enclosure dimensions	
Plate	4.5" H x 4.6" W x 0.1" D (2 gang) 11.4 cm H x 11.7 cm W x 0.3 cm D
Box	3.75" H x 3.63" W x 3.5" D 9.5 cm H x 9.2 cm W x 8.9 cm D
Boards	2.9" H x 3.5" W x 0.8" D 7.4 cm H x 8.9 cm W x 2.0 cm D (Allow at least 1.5" (3.8 cm) depth in the wall or furniture. Depth excludes connectors and knobs.)
Product weight	0.3 lbs (0.1 kg)
Shipping weight	3 lbs (1.4 kg)
Vibration	ISTA/NSTA 1A in carton (International Safe Transit Association)
Listings	UL, CUL as a component of the System 5cr Plus
Compliances	CE as a component of the System 5cr Plus
Warranty	3 years parts and labor

NOTE Specifications are subject to change without notice.

7.40-010803-D2-112012