

Specifications — SCP 150, SCP 150 AAP

Control/remote — control pad

Serial control port	RS-232, via a 3.5 mm captive screw connector, 3 pole
Baud rate and protocol	9600 baud, 8 data bits, 1 stop bit, no parity
Serial control pin configurations	A = TX, B = RX, C = GND
IR remote control	IR 402 (optional) 30' maximum, 40 degrees off axis
Program control	Extron's Simple Instruction Set (SIS™)

General

Power	12 VDC, at 0.5 A, from the System 5 IP switcher
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Rack mount	No, but furniture/wall mountable with included faceplates and electrical boxes or optional mounting bracket kits or AAP wall plates.
Enclosure type	Metal
Enclosure dimensions	
SCP 150	
Plate	4.5" H x 4.6" W x 0.1" D (2 gang) 11.4 cm H x 11.7 cm W x 0.3 cm D
Board	2.9" H x 3.5" W x 0.5" D 7.4 cm H x 8.9 cm W x 1.3 cm D [Allow at least 1.5" (3.8 cm) depth in the wall or furniture. Depth excludes connectors, knob, and buttons.]
SCP 150 AAP	
Plate	4.5" H x 8.25" W x 0.1" D (4 gang) 11.4 cm H x 11.7 cm W x 0.3 cm D
Board	2.9" H x 3.5" W x 0.5" D 7.4 cm H x 8.9 cm W x 1.3 cm D [Allow at least 1.5" (3.8 cm) depth in the wall or furniture. Depth excludes connectors, knob, and buttons.]
Product weight	0.3 lbs (0.1 kg)
Shipping weight	2 lbs (1 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Listings	UL, CUL as a component of the System 5 IP
Compliances	CE as a component of the System 5 IP
Warranty	3 years parts and labor

NOTE All nominal levels are at ±10%.

NOTE Specifications are subject to change without notice.

(7.51-020405-D5-112012)