

# Specifications — SCP 250

---

## Control/remote — control pads

IR controller module..... IR 701 (optional)

## General

Power ..... 12 VDC, at 60 mA, from a System 7SC or System 5cr Plus switcher  
Temperature/humidity ..... Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing  
Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing

### Mounting

Furniture mount..... Furniture/wall mountable with included faceplate and included mounting bracket or optional 3-gang electrical box

Enclosure type ..... Metal

### Enclosure dimensions

Faceplate..... 4.5" H x 6.4" W x 0.1" D (3-gang)  
(11.4 cm H x 16.3 cm W x 0.3 cm D)

Box..... 3.75" H x 5.4" W x 3.5" D  
(9.5 cm H x 13.8 cm W x 8.9 cm D)

Circuit board ..... 2.7" H x 5.3" W x 0.9" D  
(6.9 cm H x 13.5 cm W x 2.3 cm D)  
(Allow at least 1.5" (3.8 cm) depth in the wall or furniture. Depth excludes connectors and knobs.)

Product weight ..... 0.5 lbs (0.2 kg)

Shipping weight ..... 3 lbs (2 kg)

Vibration..... ISTA 1A in carton (International Safe Transit Association)

### Regulatory compliance

Safety..... CE, CUL, UL

EMI/EMC ..... CE, FCC Class A as components of the System 7SC

Warranty ..... 3 years parts and labor

**NOTE** All nominal levels are at  $\pm 10\%$ .

**NOTE** Specifications are subject to change without notice.

7.6-102808-D4-112012