

Specifications

TeamWork VGA Kit

Analog to Digital Converter

Video

Horizontal frequency	30 kHz to 100 kHz
Vertical frequency.....	24 Hz to 120 Hz
Resolution	640x480 to 1920x1200 or 480p, 576p, 720p, 1080i, or 1080p
Scaled resolutions.....	640x480 to 1920x1200, 480p, 576p, 720p, or 1080p

Audio

Connector	(1) 3.5 mm mini stereo (tip-ring-sleeve) jack
Impedance	>10k ohms, unbalanced, DC coupled
Input gain adjustment	-18 dBu to +10 dBu
Frequency response.....	20 Hz to 20 kHz, \pm 1.1 dB

VGA SM "Show Me" Cable

Safety.....	UL 20276, UL VW-1
Temperature rating.....	Maximum 80 °C
Voltage	30 V
Connector type	1 male 15-pin HD to 1 male 15-pin HD with an 8" (20 cm) pigtail
Material	Conductors: tinned copper Drain wire: tinned copper Jacket: PVC
Conductor gauge	Conductors and drain wire: 30 AWG
Connector dimensions.....	1.60" L x 1.23" W x 0.67" thick (40.6 mm L x 31.2 mm W x 17.0 mm thick)
Overall length.....	6' (1.8 m) measured neck-to-neck

General

Power supply.....	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 1A, 12 watts
Power consumption	14 watts, 100-240 VAC, 50-60 Hz
Enclosure dimensions	1.0" H x 8.75" W x 6.0" D (half rack wide) (2.5 cm H x 22.2 cm W x 15.2 cm D)
Regulatory compliance	
Accessibility	Complies with the appropriate requirements of Section 508 of the Rehabilitation Act (29 U.S.C. 794d).
Warranty	3 years parts and labor.

NOTES:

- For the complete specifications for each component of the kit, see www.extron.com.
- Specifications are subject to change without notice.

8.0-100413-D3