

Specifications — USB HUB4 Series

USB

USB standards	USB 2.0, USB 1.1, USB 1.0 compatible
USB data rates.....	Low speed (1.5 Mbps), full speed (12 Mbps), high speed (480 Mbps)

USB host

Number/signal type.....	1 USB
Connectors	1 female USB mini B <i>or</i> 1 female 3.5 mm captive screw connector, 5 pole (Only one port is active at a time.)

USB hub

Number/signal type.....	(1) 4 port USB
Connectors	4 female USB type A

General

Power	100 VAC to 240 VAC, 50-60 Hz, external; to 12 VDC, 1 A, regulated
Power input.....	12 VDC, 300 mA
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Mounting	
Rack mount	Yes, with optional mounting frame
Furniture mount.....	Yes with optional mounting frame or Extron devices with AAP or MAAP openings
Enclosure type	Metal
Enclosure dimensions	
USB HUB4 AAP	
Faceplate.....	1.4" H x 3.5" W x 0.1" D (3.5 cm H x 8.9 cm W x 0.3 cm D) (double space AAP plate)
Device	1.4" H x 1.4" W x 1.2" D (3.5 cm H x 3.5 cm W x 3.0 cm D) Allow at least 1.5" (3.8 cm) depth in the wall or furniture.
USB HUB4 MAAP	
Faceplate.....	1.4" H x 2.2" W x 0.1" D (3.6 cm H x 5.6 cm W x 0.3 cm D) (double space MAAP plate)
Device	1.4" H x 1.4" W x 1.2" D (3.5 cm H x 3.5 cm W x 3.0 cm D) Allow at least 1.4" (3.5 cm) depth in the wall or furniture.
Product weight	0.25 lbs (0.1 kg)
Shipping weight	1 lb (<1 kg)
Vibration.....	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Safety.....	CE, c-UL, UL
EMI/EMC	CE, C-tick, FCC Class A, ICES, VCCI Class A
Warranty	3 years parts and labor

NOTE All nominal levels are at $\pm 10\%$.

NOTE Specifications are subject to change without notice.

7.6-092209-D4-111912