

Specifications

XTP CrossPoint® CP Audio Output Board

Audio output — XTP CP 4o SA

Connectors.....	(4) 3.5 mm captive screw connector, 5 pole
Number/signal type.....	4 stereo, balanced/unbalanced
Impedance.....	50 ohms unbalanced, 100 ohms balanced
Gain error.....	±0.1 dB channel to channel
Maximum level (Hi-Z).....	>+21 dBu, balanced or unbalanced at 0.1% THD+N
Maximum level (600 ohm)	>+20 dBm, balanced or unbalanced at 0.1% THD+N
Volume control range	-75.8 to 0 dB (volume numbers 0 through 64) in a 35 dB increment from step 0 to step 1, then in 1 dB increments from steps 1 to 64; default = 64 (0 dB)

NOTE: Attenuation = volume number minus 64. The default is 0 dB = volume number 64.

General

Power	Supplied by XTP CrossPoint or XTP II CrossPoint enclosure
Power consumption.....	5 watts
Product weight	2.0 lbs (0.9 kg)
Regulatory compliance	
Environmental.....	Complies with the appropriate requirements of RoHS, WEEE.
Warranty	3 years parts and labor

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

8.1-030316-D2