

Specifications

CCB 30

General

Connector type	(3) contact closure switch to 5 pole, 3.5 mm captive screw connector on a pigtail cable
Contact rating	1A @ 24 VDC 1A @ 125 VAC

NOTE: Each switch provides momentary contact and can be used to select an input on a connected switcher. See the CCB 30 installation instructions for details.

Temperature/humidity	Storage: -13 to +158 °F (-25 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Mounting	Mounts into Cable Cubby 700 or AVEdge 100 enclosures using the provided connectivity bracket.
Enclosure type	Metal
Enclosure dimensions	
Faceplate	1.5" H x 4.2" W x 0.1" D (3.9 cm H x 10.7 cm W x 0.3 cm D)
Device	1.5" H x 4.2" W x 2.7" D (3.9 cm H x 10.7 cm W x 6.9 cm D) (Depth excludes cables.)
Product weight	0.2 lb (0.09 kg)
Shipping weight	1 lb (1 kg)
Vibration	ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance	
Environmental	Complies with the appropriate requirements of RoHS, WEEE
Warranty	3 years parts and labor

NOTE: Specifications are subject to change without notice.

8.1-112315-D3